

The A220 ink jet printer

Performance and value



Domino. Do more.

Performance and value

From the moment you press the start button the A220 delivers great value.

The clever design has reduced consumables usage while maintaining all of the strengths and value that the market has come to expect from the world's best selling Continuous lnk Jet (CIJ) printer.

The **A2**20 is capable of meeting the need for a wide range of multiple line or high speed applications onto most commonly used materials

A diverse range of applications

Domino's **A2**20 is ideal for many coding applications where multiple line or high speed coding is needed



High speed codes





Traceability codes



Clear and easy to read codes





Multiple line coding

30 years of Domino ink jet reliability doesn't happen by chance

Advanced ink from Domino

- Quality design
- Quality process
- Quality materials
- Quality people

Domino's advanced inks are at the heart of the printer ...



Greener credentials

Domino's commitment and investment in sound environmental practices means we frequently exceed the demanding governmental, industry and company standards and regulations. We are committed to minimising the consumption of natural resources and energy and the creation of waste. Additionally, our products are RoHS and WEEE compliant so that they are recyclable.

A220

The A220's efficient ink system reduces VOC emissions and advanced ink reduces waste. Weight has been reduced by 30% compared to the previous generation.

Simple to use – for stress free lines



Simple

The simple to use Field Based Editor allows you to create complex messages while reducing the need for operator training.

Secure

Eliminate coding errors with our in-built security manager.

Flexible

A wide range of print formats and speed/quality settings are all available from the simple User Interface.

Performance and value – meeting all your general purpose coding needs

Performance and value

If you require a high speed single line code of 325m/min or 5 lines of text, then the **A2**20 is the printer for you: all in a rugged stainless steel IP55 cabinet.

Your costs are kept under control through our advanced ink system with our inks delivering low MU usage and extended reservoir life.

Easy to live with – because your time is precious



Consistent

You can leave the A220 to get on with the job, through start up after start up and shut down after shut down, knowing that it will do more to perform with consistent quality.

Convenient

Just press a single button and walk away. We call it **SureStart**. It's our unique print head with a nozzle sealing and flushing process that guarantees consistent performance.

Reliable


Combined with good filtration, an independently heated head and measured viscosity control, Domino's **A2**20 does more to ensure it keeps working.







Technical Specification:

	A220
Operational Capability	
Max number of messages	300
Max number of characters per field	256
Max number of fields per message	40
Logo generation	On board
Max number of logos	250
Max number of strokes per logo	2000
Max print format height	31 drops
Max number of lines of text	5
Max line speed	325m/min
Bar codes	Linear and 2D
Interfaces	
QVGA (320x240) with key board	Standard
Ethernet (web server)	Optional
4 Stage 24V beacon	Optional
4 Stage alarm (voltage free contacts)	Optional
Programmable I/O	Optional
Product detector	Standard
Shaft encoder	Standard
Environment	
Weight	23kgs
Stainless Steel	304 or equivalent
IP Rating (designed to)	55
Operating temperature (ink dependent)	5 °C to 45°C
Humidity	10% to 90%
Power requirement	96-256v 47-63hz
Power consumption	56Watts
Compliance	
CE	Standard
RoHS	Standard
Sony Green Partner	Standard
Eupia compliant inks	Standard
Print head	
Conduit length	3m
Bend Radius	45mm
Nozzle size	60µ
SureStart	Standard
Heater	Standard
Positive air pump	Optional
Ink System	
	0251
Ink Cartridge	825ml
Ink Cartridge MU cartridge	825ml
· · · · · · · · · · · · · · · · · · ·	









Print Sample



Z#Sabsds 25 dot SXSABCDE 16 do

5X5 ABCDE 12245 7%5 ABCDE 12345 9 dot ABCDE 12345



fiayunt

9AISY807Eš6Ržý uatr<u>a</u> | | | | | | | | | | |

ABCDEF 123456 ABCDEF

7x5 TWIN LINE ABODE 12345 7x5 TWN LINE ABCDE 12345



Representative print quality only – achievable print quality dependent on substrate and printer operation conditions.



