

152 C

## Cost-effective wrap-around labelling machine

> Variety\*: Models with roller-prism or application belt

> **Applicator:** The outstanding HERMA 400

> **Flexible:** Available in standard lengths\* of:

approx. 1000/1500/2000 mm, or 40/60/80"

and three standard widths\*: 50/100/150 mm, or 2/4/6"

\*individual dimensions and solutions on request

The 152 C Standard and the 152 C Prisma – a machine range that masters every challenge of wrap-around labelling, even when confronted with tricky labelling tasks. Flexibly designed to accept an optional printing unit (hot-foil printing, for instance) as well as motorized unwinders and rewinders for a higher output capability. The tested HERMA 152 C Prisma technology guarantees precise labelling, even if the product has minor geometric variations. Spiral misalignment is practically eliminated and labelling in orientation, including twin labelling, is no longer a problem. The roller-type prism can be adjusted simply by means of a scale for different product diameters – additional change parts are now a thing of the past.









Roller-type separator and roller prism of model HERMA 152 C Prisma, easily adjustable

## Technical data of the 152 C

Products Round/cylindrical/stable

Min. Ø 20 mm (0.8") Max. Ø 140 mm (5.5") Max. Ø Prisma 100 mm (3.9")

Label size and Max. label width: 160 mm (6.3") description Max. label length: 310 mm (12.2")

Outer wound preferred

Standard reel  $\emptyset$  300 mm (12") Core  $\emptyset$  76 mm (3")

Labelling speed Product Ø 50 mm (2") 152 C (100% wrap-around): 110 products/min. (examples) Product Ø 50 mm (2") 152 C Prisma (50% wrap-around): 70 products/min.

Power supply 230V / 50 Hz / compressed air (Prisma) 4 – 6 bar (58 – 87 psi)

(electrical/pneumatic) 115 V / 60 Hz

Max. power consumption 800 VA, depending on model

We are constantly endeavouring to improve our products.

All technical data is therefore subject to change without prior notice.

HERMA GmbH Labelling Systems Division 70324 Stuttgart / Germany www.herma.com



Fax: 210 6640200

www.theodorou.gr

19002 Παιανία

marketing@theodorou.gr